

2.4 Motorised Venetian System

Technical Information

Dimensions & Limitations

1. Motor support
2. Motor
3. Tube
4. Tube support
5. Female end cap with thread
6. Male end cap with screw
7a. Head box
7b. Head box coverplate
8. Brackets

Moulded from U.V. resistant acetal.
40mm motor to suit application.
Extruded aluminium manufactured to ISO9001.
Moulded from U.V. resistant acetal.
Moulded from U.V. resistant acetal.
Powdercoated steel.
Extruded aluminium headbox.
Extruded aluminium headbox coverplate for easy access, maintenance and fitting.
Extruded aluminium manufactured to ISO9001 standard.

	ALUMINIUM	
	25mm	50mm
MINIMUM WIDTH	670mm	670mm
MAXIMUM WIDTH	3330mm	5000mm
MAXIMUM DROP	3000mm	2000mm
MAXIMUM AREA	10m ²	15m ²
STACK HEIGHT	25mm (0.034 x drop + 47mm)	
	50mm (0.050 x drop + 68mm)	
	ULTRAWOOD	
	50mm & 63mm	
MINIMUM WIDTH	650mm	
MAXIMUM WIDTH	2900mm	
MAXIMUM DROP	3000mm	
MAXIMUM AREA	5m ²	

